



World Class Printing Systems
for **Real World Applications**



GLOBALTEK BOTTOMLESS SIDE BELT TRANSFER CONVEYOR

WITH TILTING CAPABILITIES AND ENCLOSED FRAME

The GLOBALTEK™ Bottomless Conveyor has variable speeds and is used in moving containers a short distance from one working/transportation conveyor to another. Designed for open access to the bottom side of the container for coding expiration dates, lot numbers, etc. The Gripper Belts are independently adjustable using an aluminum crank handle, accommodating containers up to 8" in diameter.

FEATURES

- Made in the USA with 100% UL Certified components
- Stainless steel frame
- Up to 90 ft/min
- Pinch point protection
- Teco® variable frequency drive
- Tilting capabilities up to 45 degrees side to side

TECHNICAL SPECS


- Bodine® AC Motors, 1/6 hp, 94 rpm, 39 lb/in
- 115 volts / 1 ph / 60 hz
- Adjustable belt opening: 0" to 8"
- Belt size: 36" L x 1" H
- Floor to belt height: adjustable from 35 1/2" to 42"
- Machine dimensions: 38" L x 24 1/2" W x 44" H

OPTIONAL

- Printhead mounting bracket
- Bottle sliding plate
- Locking casters

WARRANTY

- 12 month (limited warranty)



Pinch point protection




Aluminum crank handle



Speed control



Leveling pads



Timing belt



Heavy-duty motors

